



### **Model 175 (150 / TR-38) Truck Mounted**

Depth rating - up to 8500' well servicing, 7500' workover

Truck - Freightliner class M2, 250 HP, 3 or 4 axle, Allison automatic transmission

Main drum - 38 x 10 brake rim, 7/8" Lebus, 224 clutch, water spray cooling

Sand drum - 38 x 8 brake rim, 124 clutch, 8900' of 9/16" (7200' of 5/8") capacity

	Height (ft)	Rating (lbs)	# Lines	Tubing Capacity 2-7/8" EUE (ft)	Rod Capacity (ft)
Pole -	65	60000	2	N/A	N/A
Mast -	71	150000	4	9000 (singles)	10400 (doubles)



### **Model 275 (250) Carrier or Trailer Mounted**

Depth rating - up to 8500' well servicing, 7500' workover

Carrier - alloy steel frame, 4 axle, Detroit Diesel Series 60 engine (14 L, 425 HP, Tier III), Allison 4500 OFS automatic transmission (six speed)

Main drum - 38 x 10 brake rim, 7/8" Lebus, 224 clutch, water spray cooling

Sand drum - 38 x 8 brake rim, 124 clutch, 12500' of 9/16" (10000' of 5/8") capacity

	Height (ft)	Rating (lbs)	# Lines	Tubing Capacity 2-7/8" EUE (ft)	Rod Capacity (ft)
Mast -	71	150000	4	9000 (singles)	10400 (doubles)
	71	180000	6	9000 (singles)	10400 (doubles)





### **Model 375 (350) Carrier or Trailer Mounted**

Depth rating - up to 12000' well servicing, 8000' workover, 5000' drilling

Carrier - alloy steel frame, 4 axle, Detroit Diesel Series 60 engine (14 L, 425 HP, Tier III), Allison 4500 OFS automatic transmission (six speed)

Main drum - 38 x 10 brake rim, 1" Lebus, 224 clutch, water spray cooling

Sand drum - 38 x 8 brake rim, 124 clutch, 12500' of 9/16" (10000' of 5/8") capacity

	Height (ft)	Rating (lbs)	# Lines	Tubing Capacity 2-7/8" EUE (ft)	Rod Capacity (ft)
Mast -	96	180000	4	18000 (doubles)	15600 (triples)
	96	210000	6	18000 (doubles)	15600 (triples)



### **Model 475 (450) Carrier or Trailer Mounted**

Depth rating - up to 14000' well servicing, 10000' workover, 6000' drilling

Carrier - alloy steel frame, 5 axle, Detroit Diesel Series 60 engine (14 L, 475 HP, Tier III), Allison 4500 OFS automatic transmission (six speed)

Main drum - 42 x 10 brake rim, 1" Lebus, 224 clutch, water spray cooling

Sand drum - 38 x 8 brake rim, 124 clutch, 12500' of 9/16" (10000' of 5/8") capacity

	Height (ft)	Rating (lbs)	# Lines	Tubing Capacity 2-7/8" EUE (ft)	Rod Capacity (ft)
Mast -	96	250000	6	18000 (doubles)	15600 (triples)
	104	250000	6	18000 (doubles)	15600 (triples)
	104	315000	8	18000 (doubles)	15600 (triples)

